

ATF Automatic Transmission Fluid VI

Bardahl ATF Automatic Transmission Fluid VI is a fully synthetic transmission fluid based on very high-quality base oils, specially developed for ZF 6-speed automatic transmissions. The balanced composition guarantees trouble-free operation and smooth shifting.

Applications

Mainly intended for the 6-speed automatic transmissions of ZF, as mounted in BMW, Jaguar and Land Rover, but also suitable for other OEMs that recommend this type of fluid (e.g. Audi Quattro).

Characteristics

Anti-wear protection: significantly longer transmission life. Friction properties: very smooth shifting, no vibrations. Longer oil life: excellent thermal and oxidation stability.

Accomplishments

ATF Automatic Transmission Fluid VI is an oil of superior quality developed for excellent protection and extended life of the oil and automatic transmission. The oil has excellent cold-start properties, very good shear resistance and contributes to fuel savings.

Specifications

AML - 4G4319A509/AA/S | BENTLEY - PY112995PA | BMW - 83 22 2 305 396 | BMW - 83220142516 | BMW - ATF 2 | BMW - M-1375.4 | HYUNDAI - 040000C90SG | JAGUAR - FLUID 8432 | LAND ROVER - TYK500050 | MASERATI - 231603 | VW - G 055 005 | ZF - TE-ML 11

Analysis data

Test			Results
SAE - Class	Method	Unit	ATF Automatic Transmission Fluid VI
Viscosity; cst at 100°C	ASTM D445	mm²/s	6.2
Viscosity; cst at 40°C	ASTM D445	mm²/s	31.0
Viscosity Index	ASTM D2270		153
Viscosity; cp at -40°C	ASTM D2983	mPa.s	9500
Pourpoint; °C	ASTM D6892	°C	-48
Colour	VISUAL		amber
Specific Gravity at 15/15 °C	ASTM D4052	g/ml	0.845
Flashpoint; COC; °C	ASTM D92	°C	202

Article number59655Article number59686Contents5 literContents60 liter

Article number59682Article number59692Contents25 literContents210 litres