

DSG fluid

Bardahl DSG Fluid is a 100% synthetic transmission fluid that has been specially developed for the double clutch gearbox (DCT) of modern passenger cars. This liquid guarantees trouble-free operation of these gearboxes.

Properties

- Anti-wear protection: significantly longer service life of the gearbox.
- Friction properties: very smooth shifting, no vibrations.
- Longer oil life: excellent thermal and oxidation stability.

Application

This liquid, which is mainly intended for the DSG Dual Schalt Getriebe (Double Clutch Gearbox) of the Volkswagen Group, can also be used for other OEMs that require a special product for DCT applications such as: Chrysler powershift, Mitsubishi TC-SST, BMW drivelogic 7-speed
Not for dsg with dry clutch.

Refill

With our Automatic Gearbox Dispenser you can easily change DSG Fluid (from the brands VW, Audi, Seat, Skoda and Porsche. This refreshment system is also suitable for changing automatic transmission oil from Mercedes Benz, Toyota, Ford, Volvo, BMW, Honda and Nissan. Article number of this dispenser is 00094.



Specifications

API - GL-4 | BMW - 83220306816 | BMW - 83220397244 | BMW - 83220440214 | BMW - 83222147477 | BMW - 83222148578 | BMW - 83222148579 | BMW - 83222167666 | BMW - 83222409710 | BMW - 83222433157 | BMW - DCTF-1 | BMW - DCTF-2 | BMW - DTF 1 | BMW - FFL-4 | BMW - MTF LT-3 | BMW - MTF LT-5 | CHERY - 730DHB/DHC 7DCT300 | CHERY - 738DHA 7DCT380 | CHERY - 9009011085 | CHRYSLER - 68044345EA | DAIMLER TRUCK - DTFR 13C130 | FERRARI - TF DCT-F3 | FIAT - 9.55550-DA11 | FIAT - 9.55550-MZ2 | FIAT - 9.55550-MZ6 | FORD - F-DC | FORD - WSS-M2C200-D2 | FORD - WSS-M2C200-D3 | FORD - WSS-M2C200-E1 | FORD - WSS-M2C218-A1 | FORD - WSS-M2C936-A | GM - FFL-4 | GREAT WALL - GW7DCT1 | GREAT WALL - GWM 7DCT450 | HONDA - MTF III | HYUNDAI - 04300-2N110 WDHO-1 | KIA - 04300-2N110 WDHO-1 | KUNLUN - DCTF-7S | MB - 236.21 | MB - 236.22 | MB - 236.24 | MB - 236.25 | MB - 239.21 | MB - SLS A0019898603 | MCLAREN - FFL-4 | MITSUBISHI - DIAMOND QUEEN SSTF-1 | NISSAN - 999MP-6TRTOOP | NISSAN - DCT FLUID | NISSAN - GR6 | NISSAN - GT-R R35 | NISSAN - LV MTF-1 | NISSAN - R35 SPECIAL | PORSCHE - 000.043.20 | PORSCHE - 000.043.207.29 | PORSCHE - 000.043.207.30 | PORSCHE - 000.043.305.63 | PORSCHE - 999.917.080.00 | PORSCHE - 999.917.080.01 | PORSCHE - 999.917.546.00 | PORSCHE - TF 0870 | PSA - 1618078480 | PSA - 9730 A8 | PSA - 9734 S2 | PSA - JWS 2271 | RENAULT - 7711579456 | RENAULT - 7711785243 | RENAULT - BOT450 EDC 6-SPEED | RENAULT - DC4 | RENAULT - DW5 | RENAULT - DW6 | SINOPEC - DCTF-GS | SUZUKI - 99000-22B27-036 | TOYOTA - 0888581001 | TOYOTA - JWS 2271 | TOYOTA - LF | TOYOTA - LV 75W MT | VOLVO - 1161520-7 | VOLVO - 1161839 | VOLVO - BOT341 #1161838 | VW - G 009 317 | VW - G 052 171 | VW - G 052 178 | VW - G 052 182 | VW - G 052 512 | VW - G 052 513 | VW - G 052 527 | VW - G 052 529 | VW - G 052 726 | VW - G 052 798 | VW - G 055 512 | VW - G 055 529 | VW - G 055 549 | VW - G 060 726 | VW - G 070 726 | VW - TL 521 82

Analysis data

Test			Results
SAE - Class	Method	Unit	DSG fluid
Viscosity at 100°C	ASTM D445	Cst	7.3
Viscosity at 40°C	ASTM D445	Cst	36.3
Viscosity Index	ASTM D2270		173
Viscosity; cp at -40°C	ASTM D2983	mPa.s	12100
Pourpoint; °C	ASTM D6892	°C	-51
Specific Gravity at 15/15 °C	ASTM D4052	g/ml	0.845
Flashpoint; COC; °C	ASTM D92	°C	224

Article number 59251
Contents 1 liter

Article number 59255
Contents 5 liter

Article number 59282
Contents 25 liter

Article number 59286
Contents 60 litres

Article number 59292
Contents 210 litres