



Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 1/26/2016 Revision date: 3/4/2022 Supersedes version of: 3/31/2020 Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Manual Gear Box Stop Leak
UFI : 548V-H18V-U50V-HV FY
Product code : 01756
Article number : 01756

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Consumer use
Professional use.
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV
Maxwellstraat 41
3316 GP Dordrecht
Nederland
T 0031 78 651 2322 - F 0031 78 617 4848
mjkooijman@bardahl.nl - www.bardahl.nl

1.4. Emergency telephone number

Emergency number : +31 (0) 6 54924171
During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Israel	Israel Poison Information Center Rambam Health Care Campus	6 Ha'Aliya Street 31096 Haifa	+972 4 854 1900	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for healthcare professionals

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP)

: Warning

Contains

: Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

Hazard statements (CLP)

: H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P260 - Do not breathe vapours.

P264 - Wash hands thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, eye protection/face protection.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents and container to a hazardous or special waste collection point.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	CAS-No.: 64742-65-0 EC-No.: 265-169-7 REACH-no: 01-2119471299-27	20 – 40	Asp. Tox. 1, H304

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	1 – 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
(2-methoxymethylethoxy)propanol	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	1 – 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
AMINES, POLYETHYLENEPOLY-, REACTION PRODUCTS WITH 1,3-DIOXOLAN-2-ONE AND SUCCINIC ANHYDRIDE MONOPOLYISOBUTENYL DERIVS.	CAS-No.: 147880-09-9 EC-No.: 604-611-9	< 5	Aquatic Chronic 4, H413
ethylbenzene	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	< 3	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts	CAS-No.: 68784-31-6 EC-No.: 272-238-5 REACH-no: 01-2119657973-23-0000	< 3	Eye Dam. 1, H318 Aquatic Chronic 2, H411
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	CAS-No.: 68784-26-9 EC-No.: 272-234-3 REACH-no: 01-2119524004-56	< 3	Aquatic Chronic 4, H413
Bis(nonylphenyl)amine	CAS-No.: 36878-20-3 EC-No.: 253-249-4 REACH-no: 01-2119488911-28	< 3	Aquatic Chronic 4, H413
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	CAS-No.: 682-816-2 EC-No.: 722503-68-6	< 3	Skin Sens. 1, H317 Aquatic Chronic 4, H413
toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	< 0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched substance listed as REACH Candidate (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP))	CAS-No.: 121158-58-5 EC-No.: 310-154-3 EC Index-No.: 604-092-00-9 REACH-no: 01-2119513207-49	< 0.1	Skin Corr. 1C, H314 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H- and EUH-statements: see section 16

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.
--	--

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas.
------------------	--

6.1.1. For non-emergency personnel

Emergency procedures	: Keep public away from danger area.
----------------------	--------------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
----------------------	--

6.2. Environmental precautions

Dam up the liquid spill. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Recover the product with absorbent material.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not eat, drink or smoke when using this product.
Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide local exhaust or general room ventilation.
Storage conditions : Store in a dry place. Store in a closed container. Store in a well-ventilated place.
Incompatible materials : Freezing. heat. Sources of ignition.
Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Austria - Occupational Exposure Limits	
MAK (OEL STEL)	5 mg/m ³
xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³ (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	442 mg/m ³ (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	210 mg/m ³ (Long term value)
MAK (OEL TWA) [ppm]	50 ppm (Long term value)
MAK (OEL STEL)	442 mg/m ³
MAK (OEL STEL) [ppm]	100 ppm
Belgium - Occupational Exposure Limits	
OEL TWA	221 mg/m ³ (Xylène, isomères mixtes, purs; Belgium; Time-weighted average exposure limit 8 h)

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)	
OEL TWA [ppm]	50 ppm (Xylène, isomères mixtes, purs; Belgium; Time-weighted average exposure limit 8 h)
OEL STEL	442 mg/m ³ (Xylène, isomères mixtes, purs; Belgium; Short time value)
OEL STEL [ppm]	100 ppm (Xylène, isomères mixtes, purs; Belgium; Short time value)
France - Occupational Exposure Limits	
VME (OEL TWA)	221 mg/m ³ (Xylènes, isomères mixtes, purs; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VME (OEL TWA) [ppm]	50 ppm (Xylènes, isomères mixtes, purs; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL)	442 mg/m ³ (Xylènes, isomères mixtes, purs; France; Short time value; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL) [ppm]	100 ppm (Xylènes, isomères mixtes, purs; France; Short time value; VRC: Valeur réglementaire contraignante)
Greece - Occupational Exposure Limits	
OEL TWA	435
OEL TWA [ppm]	100 ppm
OEL STEL	650 mg/m ³
OEL STEL [ppm]	150 ppm
Italy - Occupational Exposure Limits	
Local name	Xilene, isomeri misti, puro
OEL TWA	221 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	442 mg/m ³
OEL STEL [ppm]	100 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	210 mg/m ³
TGG-8u (OEL TWA) [ppm]	50 ppm
TGG-15min (OEL STEL)	442 mg/m ³
TGG-15min (OEL STEL) [ppm]	100 ppm
Spain - Occupational Exposure Limits	
Local name	Xilenos, mezcla isómeros
VLA-ED (OEL TWA) [1]	221 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL)	442 mg/m ³
VLA-EC (OEL STEL) [ppm]	100 ppm

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

xylene (1330-20-7)	
Remark	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
Remark (ACGIH)	URT & eye irr; CNS impair
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	442 mg/m ³ (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	100 ppm (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	884 mg/m ³ (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	200 ppm (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
Belgium - Occupational Exposure Limits	
OEL TWA	442 mg/m ³ (Ethylbenzène; Belgium; Time-weighted average exposure limit 8 h)
OEL TWA [ppm]	100 ppm (Ethylbenzène; Belgium; Time-weighted average exposure limit 8 h)
OEL STEL	551 mg/m ³ (Ethylbenzène; Belgium; Short time value)
OEL STEL [ppm]	125 ppm (Ethylbenzène; Belgium; Short time value)
France - Occupational Exposure Limits	
VME (OEL TWA)	88.4 mg/m ³ (Ethylbenzène; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VME (OEL TWA) [ppm]	20 ppm (Ethylbenzène; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL)	442 mg/m ³ (Ethylbenzène; France; Short time value; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL) [ppm]	100 ppm (Ethylbenzène; France; Short time value; VRC: Valeur réglementaire contraignante)

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
Greece - Occupational Exposure Limits	
OEL TWA	435 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	545 mg/m ³
OEL STEL [ppm]	125 ppm
Italy - Occupational Exposure Limits	
Local name	Etilbenzene
OEL TWA	442 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	884 mg/m ³
OEL STEL [ppm]	200 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	215 mg/m ³ (Ethylbenzeen; Netherlands; Timeweighted average exposure limit 8 h; Public occupational exposure limit value)
TGG-8u (OEL TWA) [ppm]	49 ppm (Ethylbenzeen; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
TGG-15min (OEL STEL)	430 mg/m ³ (Ethylbenzeen; Netherlands; Short time value; Public occupational exposure limit value)
TGG-15min (OEL STEL) [ppm]	97 ppm (Ethylbenzeen; Netherlands; Short time value; Public occupational exposure limit value)
Spain - Occupational Exposure Limits	
Local name	Etilbenceno
VLA-ED (OEL TWA) [1]	441 mg/m ³
VLA-ED (OEL TWA) [2]	100 ppm
VLA-EC (OEL STEL)	884 mg/m ³
VLA-EC (OEL STEL) [ppm]	200 ppm
Remark	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	441 mg/m ³ Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
WEL TWA (OEL TWA) [2]	100 ppm Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	552 mg/m ³ Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	125 ppm Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl benzene
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	URT irr; kidney dam (nephropathy)
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³ (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	384 mg/m ³ (Toluene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Toluene; EU; Short time value; Indicative occupational exposure limit value)
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m ³ Toluène; Belgium; Time-weighted average exposure limit 8 h)
OEL TWA [ppm]	20 ppm (Toluène; Belgium; Time-weighted average exposure limit 8 h)
OEL STEL	384 mg/m ³ (Toluène; Belgium; Short time value)
OEL STEL [ppm]	100 ppm (Toluène; Belgium; Short time value)
France - Occupational Exposure Limits	
VME (OEL TWA)	76.8 mg/m ³ (Toluène; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VME (OEL TWA) [ppm]	20 ppm (Toluène; France; Time-weighted average exposure limit 8 h; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL)	384 mg/m ³ (Toluène; France; Short time value; VRC: Valeur réglementaire contraignante)
VLE (OEL C/STEL) [ppm]	100 ppm (Toluène; France; Short time value; VRC: Valeur réglementaire contraignante)
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
OEL TWA [ppm]	50 ppm
OEL STEL	384 mg/m ³

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
OEL STEL [ppm]	100 ppm
Italy - Occupational Exposure Limits	
Local name	Toluene
OEL TWA	192 mg/m ³
OEL TWA [ppm]	39 ppm
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m ³ (Tolueen; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
TGG-8u (OEL TWA) [ppm]	39 ppm (Tolueen; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
TGG-15min (OEL STEL)	384 mg/m ³ (Tolueen; Netherlands; Short time value; Public occupational exposure limit value)
TGG-15min (OEL STEL) [ppm]	100 ppm (Tolueen; Netherlands; Short time value; Public occupational exposure limit value)
Spain - Occupational Exposure Limits	
Local name	Tolueno
VLA-ED (OEL TWA) [1]	192 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL)	384 mg/m ³
VLA-EC (OEL STEL) [ppm]	100 ppm
Remark	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) n° 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos"(REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido.)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	191 mg/m ³ Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	50 ppm Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	384 mg/m ³ Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
WEL STEL (OEL STEL) [ppm]	100 ppm Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	Visual impair; female repro;

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection			
Type	Field of application	Characteristics	Standard
tightly fitting safety goggles		With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Safety gloves	Nitrile rubber (NBR)				EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

Ensure good ventilation of the work station

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: red.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 61 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.885 g/cm ³ 20°C
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Open flame. Sparks. Heat. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acute toxicity (inhalation) : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 5 mg/l/4h

xylene (1330-20-7)

LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	6350 mg/l/4h

(2-methoxymethylethoxy)propanol (34590-94-8)

LD50 oral rat	5135 mg/kg
LD50 dermal rat	9500 mg/kg
LD50 dermal rabbit	9500 mg/kg

ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15415 mg/kg
LC50 Inhalation - Rat	17.8 mg/l/4h
LC50 Inhalation - Rat [ppm]	4000 ppm/4h

Bis(nonylphenyl)amine (36878-20-3)

LD50 oral rat	> 5000 mg/kg OECD 401
LD50 dermal rat	> 2000 mg/kg OECD 402

toluene (108-88-3)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	12223 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Additional information	: <3% DMSO (IP346)

toluene (108-88-3)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

(2-methoxymethylethoxy)propanol (34590-94-8)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

toluene (108-88-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

xylene (1330-20-7)	
LC50 - Other aquatic organisms [1]	8.9 – 16.4 mg/l (Pimephales promelas 96h)
EC50 - Crustacea [1]	3.2 – 9.5 mg/l (Daphnia magna) (48h)

(2-methoxymethylethoxy)propanol (34590-94-8)	
EC50 - Crustacea [1]	1919 mg/l
Threshold limit - Algae [1]	969 mg/l
Threshold limit - Algae [2]	> 969 mg/l

ethylbenzene (100-41-4)	
LC50 - Fish [2]	4.2 mg/l

Bis(nonylphenyl)amine (36878-20-3)	
LC50 - Fish [1]	> 100 mg/l OECD 203 (Danio rerio)
EC50 - Crustacea [1]	> 100 mg/l (Daphnia magna)
EC50 72h - Algae [1]	100 mg/l OECD 201 (Desmodesmus subspicitus)

toluene (108-88-3)	
LC50 - Fish [1]	24 mg/l Salmo gairdneri (Oncorhynchus mykiss)
LC50 - Fish [2]	13 mg/l Lepomis macrochirus
EC50 - Crustacea [1]	84 mg/l Locomotor effect
EC50 - Crustacea [2]	11.5 – 19.6 mg/l
Threshold limit - Algae [1]	> 400 mg/l Scenedesmus quadricauda; toxicity test
Threshold limit - Algae [2]	105 mg/l Microcystis aeruginosa

12.2. Persistence and degradability

xylene (1330-20-7)	
Persistence and degradability	Readily biodegradable.
(2-methoxymethylethoxy)propanol (34590-94-8)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

(2-methoxymethylethoxy)propanol (34590-94-8)	
ThOD	2.06 g O ₂ /g substance
BOD (% of ThOD)	0 % ThOD
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 % ThOD
Bis(nonylphenyl)amine (36878-20-3)	
Biodegradation	1 % @ 28d
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69 % ThOD
12.3. Bioaccumulative potential	
xylene (1330-20-7)	
BCF - Fish [2]	7 – 26
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.2
(2-methoxymethylethoxy)propanol (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.0043
Partition coefficient n-octanol/water (Log Kow)	< 4
ethylbenzene (100-41-4)	
BCF - Fish [1]	1
BCF - Fish [2]	15 – 79
BCF - Other aquatic organisms [1]	4.68
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.15
Bis(nonylphenyl)amine (36878-20-3)	
Partition coefficient n-octanol/water (Log Pow)	> 7.6
toluene (108-88-3)	
BCF - Fish [1]	13.2 <i>Anguilla japonica</i>
BCF - Fish [2]	90 72h; <i>Leuciscus idus</i>
BCF - Other aquatic organisms [1]	380 24h; <i>Chlorella</i> sp; Fresh weight
BCF - Other aquatic organisms [2]	4.2 4.2; <i>Mytilus edulis</i> ; Fresh weight

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 Experimental value
Bioaccumulative potential	Low.

12.4. Mobility in soil

xylene (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value

toluene (108-88-3)	
Surface tension	0.03 N/m (20°C)

12.5. Results of PBT and vPvB assessment

Component	
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Product/Packaging disposal recommendations	: Collect all waste in suitable and labelled containers and dispose according to local legislation.
Additional information	: Empty the packaging completely prior to disposal. Do not re-use empty containers.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with / / ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Clean up even minor leaks or spills if possible without unnecessary risk				

14.6. Special precautions for user

Emergency action in case of accident: : The driver shall not attempt to deal with any fire of the load, Stop the engine, No open flames. No smoking, Mark roads and warns other road users, Keep public away from danger area, NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

Other information, restriction and prohibition regulations : Detergent Regulation. aliphatic hydrocarbons \geq 30%. aromatic hydrocarbons <5%.

15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 36	Diseases caused by oils and fats of mineral or synthetic origin
RG 49	Skin disorders caused by aliphatic, alicyclic amines or ethanolamines
RG 65	Eczematiform lesions of allergic mechanism

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

France	
Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Listed in the 12. BImSchV (Annex I) under:
- Quantity threshold for operational area under § 1 para. 1

Netherlands

ABM category : Z(2) - biodegradable substances with hazardous properties for humans and the environment (carcinogenicity/ mutagenicity/reprotoxicity/bioacumulative potential or toxicity)
SZW-lijst van kankerverwekkende stoffen : Distillates (petroleum), solvent-dewaxed heavy paraffinic, Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts, Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased, phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched are listed
SZW-lijst van mutagene stoffen : Distillates (petroleum), solvent-dewaxed heavy paraffinic, Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 1,3-dimethylbutyl) esters, zinc salts, Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased, phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : xylene, toluene are listed

Denmark

Class for fire hazard : Class III-1
Store unit : 50 liter
Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
Danish National Regulations (Additional) : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
2.2	Precautionary statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Abbreviations and acronyms:

Abbreviations and acronyms:

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail

ICAO: International Civil Aviation Organization

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360F	May damage fertility.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Manual Gear Box Stop Leak

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:	
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Repr. 1B	Reproductive toxicity, Category 1B
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.