

ATF IV Automatic Transmission Fluid Type: Dexron IV/ Mercon

Bardahl Automatic Transmission Fluid IV is a high-quality automatic transmission fluid developed for use in the new generation of automatic gearboxes, where a Dexron III or Mercon type is prescribed. This oil has been specially developed for electronically controlled transmissions that often have to operate under high temperatures. The following properties are of great importance.

- A very good oxidation stability
- A high and stable viscosity index
- An extraordinarily low solidification point
- Good protection against wear, corrosion and foaming
- Reconditioned gaskets and seals

This oil can be mixed with any brand of automatic transmission fluid and can be used all year round.

Application

Suitable for new (remanufactured) automatic gearboxes and/or higher mileage, power steering, torque converters and all kinds of other applications for which a type **ATF Dexron II-D, Dexron II-E, or Dexron III** is prescribed.

Refill

With our Automatic Gearbox Dispenser you can easily change ATF oil (from the brands VW, Audi, Seat, Skoda and Porsche. This refresher system is also suitable for changing automatic transmission oil from Mercedes Benz, Toyota, Ford, Volvo, BMW, Honda and Nissan. Article number of this dispenser is **00094**.



Specifications

AISIN-WARNER - JWS 3309 | AISIN-WARNER - JWS 3314 | AISIN-WARNER - JWS 3317 | ALFA ROMEO - HP20 | ALLISON - C4 | ALLISON - TES 295 | ALLISON - TES 389 | BMW - 81 22 9 400 275 | BMW - 81 22 9 401 220 | BMW - 83 22 0 026 922 | BMW - 83 22 0 403 248 | BMW - 83 22 0 403 249 | BMW - 83 22 2 355 599 | BMW - 83 22 9 407 765 | BMW - ATF 6 | BMW - ETL 7045E | BMW - ETL 8072B | BMW - LA 2634 | BMW - LT 71141 | CHRYSLER - AS68RC ATF | CHRYSLER - ATF +3 AND +4 | CHRYSLER - MS 9602 | DAIMLER TRUCK - DTFR 13C100 | DAIMLER TRUCK - DTFR 13C110 | DAIMLER TRUCK - DTFR 13C140 | DAIMLER TRUCK - DTFR 13C150 | DAIMLER TRUCK - DTFR 13C170 | DAIMLER TRUCK - DTFR 13C180 | FIAT - 9.55550-AV1 | FIAT - 9.55550-AV4 | FORD - MERCON | FORD - MERCON V | FORD - WSS-M2C195-A | FORD - WSS-M2C919-E | FORD - WSS-M2C922-A1 | GM - DEXRON II-D | GM - DEXRON II-E | GM - DEXRON III-G | GM - DEXRON III-H | HONDA - ATF Z-1 | HYUNDAI - ATF RED 1K | HYUNDAI - SP-II | HYUNDAI - SP-III | JAGUAR - JLM 20292 (LA 3403-M115) | JAGUAR - JLM 21044 | JASO - M315, CLASS 1A | LAND ROVER - LR002748 | LAND ROVER - N402 | MAZDA - ATF F-1 | MAZDA - MV TYPE M5 | MB - 236.10 | MB - 236.11 | MB - 236.3 | MB - 236.5 | MB - 236.6 | MB - 236.7 | MB - 236.8 | MB - 236.9 | MB - 236.91 | MITSUBISHI - 4030401 | MITSUBISHI - ATF J2 | MITSUBISHI - DIA QUEEN ATF-PA | MITSUBISHI - V5AWF | NISSAN - 999MP-ATFD3MP | NISSAN - MATIC-D | NISSAN - MATIC-J | NISSAN - MATIC-K | NISSAN - MATIC-W | PORSCHE - LA 3403-M115 | PSA - P/N Z 000169756 | RENAULT - MATIC-D2 | TOYOTA - TYPE T | TOYOTA - TYPE T-III | TOYOTA - TYPE T-IV | VOLVO - 1161540 | VOLVO CONSTR. EQUIP. (VCE) - 1273.41 | VW - G 052 025 | VW - G 052 055 | VW - G 052 162 | VW - G 052 533 | VW - G 052 990 | VW - G 055 025 | VW - G US 000 162 | ZF - TE-ML 11A | ZF - TE-ML 11B

Analysis data

SAE - Class	Test		Results
	Method	Unit	ATF IV
Viscosity, mm ² /s at 100°C	ASTM D445	mm ² /s	8.1
Viscosity, mm ² /s at 40°C	ASTM D445	mm ² /s	35.6
Viscosity index	ASTM D2270		212
Viscosity, mPa.s at -40°C	ASTM D2983	mPa.s	12563
Pourpoint; °C	ASTM D6892	°C	-51°
Density at 15/15 °C	ASTM D4052	g/ml	0.870
Flashpoint	ASTM D92	°C	185
Colour	VISUAL		ed

Article number 52651

Contents 1 liter

Article number 52686

Contents 60 liter

Article number 52655

Contents 5 liter

Article number 52692

Contents 210 litres

Article number 52682

Contents 25 liter