

XTM Motorcycle Oil 20W50 Multigrade

Bardahl XTM 20W50 Multigrade is a modern multigrade engine oil that is tuned to today's 4-stroke engines and gearboxes of motorcycles.

The special composition of this motorcycle oil makes it possible for engines to function optimally under the most diverse conditions. The oil is made up of high-quality base oils, with special cleansing, dispersing and anti-wear components. In summary, this oil provides the following properties:

- A very high resistance to oxidation.
- Prevents black sludge
- A very good protection against wear, corrosion and foaming.
- Strong cleansing and dispersing properties.
- A high, stable viscosity index

This engine oil is suitable for long oil drain intervals and can be used all year round. Tests have shown that the active ingredients in this oil retain their property even under the most unfavorable conditions of use.

Manual

XTM Multigrade Motorcycle Oil is miscible with all mineral oils. It is suitable for engines with a wet clutch.

Specifications

API - SG/CD | MIL - L-46152 E

Analysis data

Test			Average result
SAE class	Method	Unit	20w50 multigrade
Viscosity; At 100°C	ASTM D445	mm²/s	18.1
Viscosity; At 40°C	ASTM D445	mm²/s	166
Viscosity; cp at-15°C	ASTM D5293	mPa.s	8500
Viscosity Index	ASTM D2270		133
Straight Ash:w		wt.%	1.05
Sulphated Ash;	ASTM D874	wt.%	0.6
TAN	ASTM D664	mg KOH/g	2.7
tbn	ASTM D2896	mg KOH/g	5.3
pourpoint	ASTM D6892	°C	-24
Color	ASTM D1500		7.0
Flashpoint	ASTM D92	°C	235
Specific Gravity at 15/15°C	ASTM D4052	g/ml	0.895
Noack Evaporation;		wt.%	11.0

PRODUCT INFORMATION



Article number 55351 Contents 1 liter

Article number 55355 Contents 5 liter

Article number 55382 Contents 25 liter

Article number 55386 **Contents** 60 liter

Article number 55392 Contents 210 litres