

XTM Motor Oil 10W40 Multigrade Semi-Synthetic

Bardahl XTM 10W40 semi synthetic has been developed especially for the lubrication of motorcycle engines. The use of this synthetic reinforced oil ensures that at very low and very high temperatures there is always a protective, strong lubricating film on the engine parts. This oil exceeds the APIs highest requirements for motorcycles.

Bardahl XTM 10W40 semi synthetic is formulated from high-quality synthetic and mineral base oils with a balanced package of refined additives. This engine oil contains viscosity index improvers to allow safe and easy cold weather starts and provides complete protection during engine heating.

Bardahl XTM 10W40 semi synthetic has excellent protection against abrasion, rust, oxidation, corrosion, and precipitation in the combustion chamber. This oil provides very good lubrication and engine protection over a wide range of operating temperatures and conditions.

This oil is approved for use in all kinds of 4-stroke motorcycle engines. It exceeds the warranty requirements of motorcycle manufacturers.

Specifications

API - SL | JASO - MA2

Analysis data

SAE-class	Test		Results
	Method	Unit	XTM Motor Oil 10W40 Multigrade Semi-Synthetic
Viscosity; At 100°C	ASTM D445	Cst	13.8
Viscosity; At 40°C	ASTM D445	Cst	90
Viscosity; cp at -20°C			3300
Viscosity Index	ASTM D2270		155
Sulphated Ash;		wt. %	0.85
TAN	ASTM D664	mg KOH/g	2.3
tbn	ASTM D2896	mg KOH/g	9.1
pourpoint	ASTM D6892	°C	-39
Flashpoint	ASTM D92	°C	224
Specific Gravity at 15/15°C	ASTM D4052	Kg/ltr	0.876
Noack Evaporation;		wt. %	11.0

Article number 55051
Contents 1 liter

Article number 55082
Contents 25 liter

Article number 55055
Contents 5 liter

Article number 55086
Contents 60 liter

Article number 55092
Contents 210 litres