



EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 06/12/2019 Revision date: 06/12/2019 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : EGR Valve Cleaner KIT (aerosol)
UFI : EKN4-W8D0-800G-WUPU
Product code : 9123
Type of product : Aerosol
Vaporizer : Aerosol
Article number : 9123-2

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Professional use.
Consumer use
Function or use category : Aerosol propellants

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BARDAHL NL - OCD NEDERLAND BV
Maxwellstraat 41
3316 GP Dordrecht
Nederland
T 0031 78 651 2322 - F 0031 78 617 4848
mjkooijman@bardahl.nl - www.bardahl.nl

1.4. Emergency telephone number

Emergency number : +31 (0) 6 54924171
During office hours: 8.30 t/m 17:00 h

Country	Official advisory body	Address	Emergency number	Comment
	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Repeated exposure, Category 2 H373
Aspiration hazard, Category 1 H304
Full text of H- and EUH-statements: see section 16

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

Signal word (CLP)

: Danger

Contains

: xylene

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (CLP)

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P260 - Do not breathe gas, mist.

P264 - Wash hands thoroughly after handling.

P280 - Wear protective gloves, eye protection/face protection.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P501 - Dispose of contents/container to a facility for the collection of hazardous or special waste.

P210 - Keep away from heat, hot surfaces, sparks, open flames, Sources of ignition. – No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container: Do not pierce or burn, even after use.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Extra phrases

: Not overly spraying, only use for its original purpose.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments

: aliphatic hydrocarbons $\geq 30\%$
aromatic hydrocarbons 5-15%

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8 REACH-no: 01-2119471330-49	15 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
xylene (Note C)	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216-32	5 – 15	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
4-hydroxy-4-methylpentan-2-one; diacetone alcohol	CAS-No.: 123-42-2 EC-No.: 204-626-7 EC Index-No.: 603-016-00-1 REACH-no: 01-2119473975-21	< 10	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
ethylbenzene	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	< 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304
toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3 REACH-no: 01-2119471310-51	≤ 0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
4-hydroxy-4-methylpentan-2-one; diacetone alcohol	CAS-No.: 123-42-2 EC-No.: 204-626-7 EC Index-No.: 603-016-00-1 REACH-no: 01-2119473975-21	(10 ≤ C < 100) Eye Irrit. 2, H319

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove contaminated clothing immediately. Wash skin with plenty of water. Wash contaminated clothing before reuse.

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after inhalation	: Shortness of breath. May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Water haze. Foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Hazardous decomposition products in case of fire	: Incomplete combustion will generate poisonous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Evacuate area. Ensure adequate ventilation, especially in confined areas. Keep public away from danger area. Equip cleanup crew with proper protection.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Dike for recovery or absorb with appropriate material.

6.3. Methods and material for containment and cleaning up

For containment	: Recover the product with absorbent material.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13: "Disposal considerations".

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Extremely flammable aerosol. Pressurised container: May burst if heated. Do not pierce or burn, even after use.
Precautions for safe handling	: Do not eat, drink or smoke when using this product. Provide good ventilation in process area to prevent formation of flammable vapour. For further information refer to section 8: "Exposure controls/personal protection". Do not spray on an open flame or other ignition source. Container under pressure. Do not drill or burn even after use.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Provide local exhaust or general room ventilation.
Incompatible materials	: Freezing.
Heat and ignition sources	: Do not expose to temperatures exceeding 50 °C/ 122 °F.
Information on mixed storage	: Keep away from food, drink and animal feeding stuffs.
Storage area	: Store in a well-ventilated place. Store in a dry place.
Special rules on packaging	: Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

acetone; propan-2-one; propanone (67-64-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Acetone
IOEL TWA	1210 mg/m ³
IOEL TWA [ppm]	500 ppm
ethylbenzene (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	442 mg/m ³ (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	100 ppm (Ethylbenzene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	884 mg/m ³ (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	200 ppm (Ethylbenzene; EU; Short time value; Indicative occupational exposure limit value)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	441 mg/m ³ Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
WEL TWA (OEL TWA) [2]	100 ppm Ethylbenzene; United Kingdom; Timeweighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	552 mg/m ³ Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	125 ppm Ethylbenzene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³ (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Toluene; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	384 mg/m ³ (Toluene; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Toluene; EU; Short time value; Indicative occupational exposure limit value)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	191 mg/m ³ Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL TWA (OEL TWA) [2]	50 ppm Toluene; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL)	384 mg/m ³ Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
WEL STEL (OEL STEL) [ppm]	100 ppm Toluene; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
xylene (1330-20-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	221 mg/m ³ (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL TWA [ppm]	50 ppm (Xylene, mixed isomers, pure; EU; Timeweighted average exposure limit 8 h; Indicative occupational exposure limit value)
IOEL STEL	442 mg/m ³ (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)
IOEL STEL [ppm]	100 ppm (Xylene, mixed isomers, pure; EU; Short time value; Indicative occupational exposure limit value)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

No additional information available

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

8.2.2.3. Respiratory protection

Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Good ventilation of the workplace required

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: > 35 °C
Flammability	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 21 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: < 20.5 mm ² /s 40°C
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.84

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 48 %

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.

10.2. Chemical stability

Stable under normal conditions. Contains gas under pressure; may explode if heated.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Open flame. Sparks. Heat. Water, humidity. Freezing.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

acetone; propan-2-one; propanone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	7800 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15415 mg/kg
LC50 Inhalation - Rat	17.8 mg/l/4h
LC50 Inhalation - Rat [ppm]	4000 ppm/4h
toluene (108-88-3)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	12223 mg/kg

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

toluene (108-88-3)	
LC50 Inhalation - Rat	> 20 mg/l/4h
xylene (1330-20-7)	
LD50 oral rat	4300 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	6350 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
acetone; propan-2-one; propanone (67-64-1)	
LOAEL (oral, rat)	5800 mg/kg bodyweight OECD 401
LOAEL (dermal, rat/rabbit)	2000 mg/kg bodyweight OECD 402
LOAEC (inhalation, rat, gas)	30000 ppmv/4h
LOAEC (inhalation, rat, vapour)	71 mg/l/4h
STOT-single exposure	May cause drowsiness or dizziness.
toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
4-hydroxy-4-methylpentan-2-one; diacetone alcohol (123-42-2)	
STOT-single exposure	May cause respiratory irritation.
xylene (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
toluene (108-88-3)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
xylene (1330-20-7)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
EGR Valve Cleaner KIT (aerosol)	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm ² /s 40°C

11.2. Information on other hazards

No additional information available

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified
(acute)

Hazardous to the aquatic environment, long-term : Not classified
(chronic)

acetone; propan-2-one; propanone (67-64-1)

LC50 - Fish [1]	6210 mg/l Pimephales promelas; normal concentration
LC50 - Fish [2]	5540 mg/l Salmo gairdneri (Oncorhynchus mykiss)
EC50 - Crustacea [1]	8800 mg/l
TLM - Fish [1]	13000 ppm 96h Gambusia affinis; Turbulent water
TLM - Fish [2]	> 1000 ppm 96h Pisces
Threshold limit - Other aquatic organisms [1]	3000 mg/l Plankton
Threshold limit - Other aquatic organisms [2]	28 mg/l Protozoa
Threshold limit - Algae [1]	7500 mg/l Scenedesmus quadricauda; pH=7
Threshold limit - Algae [2]	3400 mg/l 48h Chlorella sp.

ethylbenzene (100-41-4)

LC50 - Fish [2]	4.2 mg/l
-----------------	----------

toluene (108-88-3)

LC50 - Fish [1]	24 mg/l Salmo gairdneri (Oncorhynchus mykiss)
LC50 - Fish [2]	13 mg/l Lepomis macrochirus
EC50 - Crustacea [1]	84 mg/l Locomotor effect
EC50 - Crustacea [2]	11.5 – 19.6 mg/l
Threshold limit - Algae [1]	> 400 mg/l Scenedesmus quadricauda; toxicity test
Threshold limit - Algae [2]	105 mg/l Microcystis aeruginosa

xylene (1330-20-7)

LC50 - Other aquatic organisms [1]	8.9 – 16.4 mg/l (Pimephales promelas 96h)
EC50 - Crustacea [1]	3.2 – 9.5 mg/l (Daphnia magna) (48h)

12.2. Persistence and degradability

acetone; propan-2-one; propanone (67-64-1)

Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 % ThOD 20 days

ethylbenzene (100-41-4)

Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 % ThOD
toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69 % ThOD
xylene (1330-20-7)	
Persistence and degradability	Readily biodegradable.
12.3. Bioaccumulative potential	
acetone; propan-2-one; propanone (67-64-1)	
BCF - Fish [1]	0.69 Pisces
BCF - Other aquatic organisms [1]	3
Partition coefficient n-octanol/water (Log Pow)	-0.24 Test data
Bioaccumulative potential	Not established.
ethylbenzene (100-41-4)	
BCF - Fish [1]	1
BCF - Fish [2]	15 – 79
BCF - Other aquatic organisms [1]	4.68
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.15
toluene (108-88-3)	
BCF - Fish [1]	13.2 Anguilla japonica
BCF - Fish [2]	90 72h; Leuciscus idus
BCF - Other aquatic organisms [1]	380 24h; Chlorella sp; Fresh weight
BCF - Other aquatic organisms [2]	4.2 4.2; Mytilus edulis; Fresh weight
Partition coefficient n-octanol/water (Log Pow)	2.73 Experimental value
Bioaccumulative potential	Low.
xylene (1330-20-7)	
BCF - Fish [2]	7 – 26
Bioconcentration factor (BCF REACH)	< 500
Partition coefficient n-octanol/water (Log Pow)	3.2
12.4. Mobility in soil	
ethylbenzene (100-41-4)	
Surface tension	0.029 N/m

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethylbenzene (100-41-4)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
toluene (108-88-3)	
Surface tension	0.03 N/m (20°C)
xylene (1330-20-7)	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Product/Packaging disposal recommendations	: Collect all waste in suitable and labelled containers and dispose according to local legislation. Dispose used or damaged aerosol cans at permitted disposal sites.
Additional information	: Empty the packaging completely prior to disposal. Do not re-use empty containers.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 16 05 04* - gases in pressure containers (including halons) containing dangerous substances

SECTION 14: Transport information

In accordance with / / ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable, containing substances in Class 8, Packing Group II	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, containing substances in Class 8, Packing Group II, 2.1 (8)	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1 (8)	2.1	2.1

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
		Not applicable		
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

Air transport

PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: Forbidden
PCA max net quantity (IATA)	: Forbidden
CAO packing instructions (IATA)	: Forbidden
CAO max net quantity (IATA)	: Forbidden
ERG code (IATA)	: 10C

Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 19, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : aliphatic hydrocarbons $\geq 30\%$. aromatic hydrocarbons. 5-15%.

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I
Toluene		108-88-3	2902 30 00	Category 3		Annex I

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Abbreviations and acronyms:

Abbreviations and acronyms:

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail
ICAO: International Civil Aviation Organization
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

EGR Valve Cleaner KIT (aerosol)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.